



NeoSapphire

NS3602 All-Flash Array

- Superior performance with 420K IOPS for 4KB random write in a compact 1U form factor
- Dual port Fibre Channel interface for easy integration with SAN environment
- Enterprise SAS endurance SSDs
- Ranked¹ #3 with an excellent \$0.20/SPC-1 IOPS™





NeoSapphire 3602 All-Flash Array

SPECIFICATIONS

Form Factor	1U rack mount
IOPS for 4KB Random Write	420K sustained
Flash Management	FlexiRemap technology
Usable Capacity ²	2TB
Number of SSD	10 x hot-swappable SSD
Flash Type	MLC
Connectivity	2 x 16G Fibre Channel LC SFP+
Storage Protocol	Fibre Channel
Management Interface	Web-based management interface (via HTTP/HTTPS) CLI (via serial port)
Power Supply	700W/750W 1+1 redundant
Feature Highlight	<ul style="list-style-type: none"> • Optimized low-latency performance for SANs • High performance in compact form factor • Data protection through redundancy
Dimensions (W x D x H)	437mm x 597mm x 43mm (17.2in x 23.5in x 1.7in)
Net Weight ³	13.5kg (29.8lb)
Environmental Temperature	Operating: 10°C to 35°C Storage (non-operating): -20°C to 60°C
Environmental Humidity	Operating: 10% to 90% non-condensing Storage (non-operating): 5% to 95% non-condensing

¹ The SPC-1 Executive Summary and Full Disclosure Report for the NeoSapphire 3602 are available at:

http://www.storageperformance.org/results/benchmark_results_spc1_active/#a00183

² Usable capacity refers to the approximation of the storage capacity that users can have. The accurate usable capacity may vary depending on software configurations and other factors.

³ Weight may vary depending on components and manufacturing variability.

©2015-2017. All rights reserved. AcceleStor, FlexiRemap, and NeoSapphire are trademarks or registered trademarks of AcceleStor, Inc. in the United States of America and/or other countries. Other names and brands may be claimed as the property of others. Pictures are not contractual. In a continuing effort to improve the quality of our products, information in this brochure is subject to change without notice. Images appearing are only representations of some of the configurations available. Availability may vary depending on region. AcceleStor, Inc. reserves the right to the interpretation of the above specifications, terms and conditions.